LPES INTERNATIONAL
Web. www.lpesinternational.com
Email. info@lpes.in & info@lpesinternational.com

TECHNICAL DATA SHEET

COMPONENT ART :
LPES- 011008130

Component Description:

12 mm GI Round Conductor:

LPES Non Insulated/Bare Mild Steel Galvanised Iron 76 - 100 micron Round Solid 12mm Conductor Design & Comply As Per IEC-62305,NBC-2016 & IEEE-80 Tested As Per IEC-62561-2 Part No. 011008130 Article No.LPES-CD-SO-R-MS-12mm-GI-76_100-BA

UV resistant. Classification H1.
Use for Lightning Protection Class I-II-III-IV.

Additional components:
Classified Holders of Liner and Fix motion.

Installation:

Down and Ground termination system of Overhead and integrated systems.

Dimensions:

Cross Section of Fl :	113.1 mm²
Size / Ø :	12 mm
Coating Thickness	100 micron
Ends :	Round
Material :	St/t Zn

Characteristic:

Material thickness / Coating :	12 mm/100 micron
Electrical Resistivity ρ :	0.143 μΩ·m
Tensile Strength:	>300 N/mm²
Electrical Conductivity:	>54% IACS
Electro magic Compatibility:	Passive
Weight :	1 kg/m

Standard:

IEC EN

62561-2:2017

Tests:

- Environmental Test
  - Salt mist (EN 60068-2-52:1996)
  - Humid sulphurous atmosphere (ISO 6988:1985)
- Thickness Coating of Conductors ISO 1460 ISO1461 ISO 2178
- Bend and Adhesion Test
- Tensile Test ISO 6892-1
- Electrical Resistivity Test
- Marking Tests
- EMC Test