

TECHNICAL DATA SHEET



COMPONENT ART :
LPES- 011009130

Component 14 mm GI Round Conductor:

Description: LPES Non Insulated/Bare Mild Steel Galvanised Iron 76 - 100 micron Round Solid 14mm Conductor Design & Comply As Per IEC-62305,NBC-2016 & IEEE-80 Tested As Per IEC-62561-2 Part No. 011009130 Article No.LPES-CD-SO-R-MS-14mm-GI-76_100-BA

UV resistant. Classification H1.
Use for Lightning Protection Class I-II-III-IV.

Additional components:
Classified Holders of Liner and Fix motion.

Installation: Down and Ground termination system of Overhead and integrated systems.

Dimensions:	Cross Section of FI :	153.9 mm ²
	Size / Ø :	14 mm
	Coating Thickness	100 micron
	Ends :	Round
	Material :	St/t Zn

Characteristic:	Material thickness / Coating :	14 mm/100 micron
	Electrical Resistivity ρ :	0.143 $\mu\Omega \cdot m$
	Tensile Strength:	>300 N/mm ²
	Electrical Conductivity:	>54% IACS
	Electro magic Compatibility:	Passive
	Weight :	1.4 kg/m

Standard:

IEC EN

62561-2:2017

Tests:

- Environmental Test
 - ♦ Salt mist (EN 60068-2-52:1996)
 - ♦ Humid sulphurous atmosphere (ISO 6988:1985)
- Thickness Coating of Conductors ISO 1460 ISO1461 ISO 2178
- Bend and Adhesion Test
- Tensile Test ISO 6892-1
- Electrical Resistivity Test
- Marking Tests
- EMC Test